BOROUGH OF ROCKLEIGH ORDINANCE #2023-2

AN ORDINANCE TO ESTABLISH REGULATIONS PERTAINING TO PRIVATE STORM DRAIN INLETS AND ESTABLISHING STANDARDS FOR RETROFITTING AND TO PRESCRIBE PENALTIES FOR THE VIOLATION THEREOF.

BE IT ORDAINED by the Mayor and Council of the Borough of Rockleigh, in the County of Bergen, and State of New Jersey as follows:

Section 1. Purpose.

This Ordinance is intended to require the retrofitting of existing storm drain inlets which are in direct contact with repaving, repairing, reconstruction, or resurfacing or alterations of facilities on private property, to prevent the discharge of solids and floatables (such as plastic bottles, cans, food wrappers and other litter) to the municipal separate storm sewer system(s) operated by the Borough of Rockleigh so as to protect public health, safety and welfare, and to prescribe penalties for the failure to comply.

Section 2. Definitions.

For the purpose of this Ordinance, the following terms, phrases, words, and their derivations shall have the meanings stated herein unless their use in the text of this Chapter clearly demonstrates a different meaning. When not inconsistent with the context, words used in the present tense include the future, words used in the plural number include the singular number, and words used in the singular number include the plural number. The word "shall" is always mandatory and not merely directory.

MUNICIPAL SEPARATE STORM SEWER SYSTEM (MS4)

A conveyance or system of conveyances (including roads with drainage systems, municipal streets, catch basins, curbs, gutters, ditches, manmade channels, or storm drains) that is owned or operated by the Borough of Rockleigh or other public body, and is designed and used for collecting and conveying stormwater.

PERSON

Any individual, corporation, company, partnership, firm, association, or political subdivision of this State subject to municipal jurisdiction.

STORM DRAIN INLET

An opening in a storm drain used to collect stormwater runoff and includes, but is not limited to, a grate inlet, curb-opening inlet, slotted inlet, and combination inlet.

WATERS OF THE STATE

Shall mean the ocean and its estuaries, all springs, streams and bodies of surface or ground water, whether natural or artificial, within the boundaries of the State of New Jersey or subject to its jurisdiction.

Section 3. Prohibited Conduct.

No person in control of private property (except a residential lot with one single family house) shall authorize the repairing, repairing (excluding the repair of individual potholes), resurfacing (including top coating or chip sealing with asphalt emulsion or a thin base of hot bitumen), reconstructing or altering any surface that is in direct contact with an existing storm drain inlet on that property unless the storm drain inlet either:

- a. Already meets the design standard below to control passage of solid and floatable materials; or
- b. Is retrofitted or replaced to meet the standard in Section 4 below prior to the completion of the project.

Section 4. Design Standard.

Storm drain inlets identified in Section 3 above shall comply with the following standard to control passage of solid and floatable materials through storm drain inlets. For purposes of this paragraph, "solid and floatable materials" means sediment, debris, trash, and other floating, suspended, or settleable solids. For exemptions to this standard see Section 4c below.

- a. Design engineers shall use either of the following grates whenever they use a grate in pavement or another ground surface to collect stormwater from that surface into a storm drain or surface water body under that grate:
 - The New Jersey Department of Transportation (NJDOT) bicycle safe grate, which is described in Chapter 2.4 of the NJDOT Bicycle Compatible Roadways and Bikeways Planning and Design Guidelines (April 1996); or
 - 2. A different grate, if each individual clear space in that grate has an area of no more than seven (7.0) square inches, or is no greater than 0.5 inches across the smallest dimension.

Examples of grates subject to this standard include grates in grate inlets, the grate portion (non-curb-opening portion) of combination inlets, grates on storm sewer manholes, ditch grates, trench grates, and grates of spacer bars in slotted drains. Examples of ground surfaces include surfaces of roads (including bridges), driveways, parking areas, bikeways, plazas, sidewalks, lawns, fields, open channels, and stormwater basin floors.

b. Whenever design engineers use a curb-opening inlet, the clear space in that curb opening (or each individual clear space, if the curb opening has two or more clear spaces) shall have an area of no more than seven (7.0) square inches, or be no greater than two (2.0) inches across the smallest dimension.

- c. This standard does not apply:
 - 1. Where the municipal engineer agrees that this standard would cause inadequate hydraulic performance that could not practicably be overcome by using additional or larger storm drain inlets that meet these standards;
 - 2. Where flows are conveyed through any device (e.g., end of pipe netting facility, manufactured treatment device, or a catch basin hood) that is designed at a minimum, to prevent delivery of all solid and floatable materials that could not pass through one of the following:
 - (a) A rectangular space four and five-eighths inches long and one and one-half inches wide (this option does not apply for outfall netting facilities); or
 - (b) A bar screen having a bar spacing of 0.5 inches.
 - 3. Where flows are conveyed through a trash rack that has parallel bars with one-inch (1") spacing between the bars; or
 - 4. Where the New Jersey Department of Environmental Protection determines, pursuant to the New Jersey Register of Historic Places Rules at N.J.A.C. 7:4-7.2(c), that action to meet this standard is an undertaking that constitutes an encroachment or will damage or destroy the New Jersey Register listed historic property.

Section 5. Enforcement.

This Ordinance shall be enforced by the Police Department providing police services to the Borough of Rockleigh and/or such other municipal officials as may be designated by the Mayor and Council.

Section 6. Penalties.

Any person who is convicted of violating any provision of this Ordinance shall be subject to such fine and general penalty as set forth in §1-5, General Penalty, of the Code of the Borough of Rockleigh, within the discretion of the Municipal Court Judge.

Section 7. Severability.

If any section, sentence or any part of this Ordinance is adjudged unconstitutional or invalid, such judgment shall not effect, impair or invalidate the remainder of this Ordinance but shall be confined in its effect to the section, sentence or other part of this Ordinance directly involved in the controversy which such subject shall be rendered.

Section 8. Inconsistent Ordinances Repealed.

All ordinances or parts of ordinances which are inconsistent with the provisions of this ordinance are hereby repealed, but only to the extent of such inconsistencies.

Section 9. Effective Date.

This Ordinance shall take effect after publication thereof and final passage as required by law.

JAMES PONTONE, Mayor

MARCELLA GIAMPICCOLO, RMC

Borough Clerk

Introduced: March 6, 2023 Adopted: April 3, 2023 Approved: April 3, 2023